



**Star Manufacturing
International Inc.**

10 Sunnen Drive
P.O. Box 430129
St. Louis, MO 63143

Phone: (800) 264-7827
(314) 781-5353 (Int'l)
FAX: (800) 264-6666
(314) 781-4344 (Int'l)
www.star-mfg.com

**JetStar
6 Oz. Poppers**

**Model 39-A
Model 39D-A
Model 39R-A
Model 39S-A**

JetStar Popcorn Poppers Built to last...Designed to Perform

Sturdy Construction

Handsome 4 corner post construction stands up to heavy commercial use. Excellent merchandising is achieved with clear tempered glass panels, heavy gauge plexiglass doors with full length aluminum hinges to provide unobstructed view. A clear lexan serving drop panel provides for great visibility, even when machine is located on a back counter. Colorful graphics are supplied and may be applied to either side of the machine to build impulse sales.

Models

- 39-A - **JetStar** Popper with Yellow Painted Top
- 39D-A - **JetStar** Popper with Wood-Grain Styling
- 39R-A - **JetStar** Popper with Antique Styling
- 39S-A - **JetStar** Popper with Stainless Steel Top

Performance Features

A 1000 Watt element and design of the popping kettle provides for excellent popping performance even from a cold start. The nickel plated steel kettle cleans easily and has a one piece kettle lid with magnet catch that makes loading the kettle easy and safe. Heated corn deck and stainless steel old maid drawer keeps maintenance to a minimum. Eye level switches, wire cage protected display lamp, and a 6 ft. lead in cord and plug are all standard.

Warranty

JetStar poppers are backed by a 2 year parts and labor warranty on models 39-A, 39D-A, 39R-A, and 39S-A sold and operated within the Continental U.S.





**Star Manufacturing
International Inc.**

10 Sunnen Drive
P.O. Box 430129
St. Louis, MO 63143

Phone: (800) 264-7827
(314) 781-5353 (Int'l)
FAX: (800) 264-6666
(314) 781-4344 (Int'l)
www.star-mfg.com

**JetStar
6 Oz. Poppers**

**Model 39-A
Model 39D-A
Model 39R-A
Model 39S-A**

**JetStar Popcorn Poppers
Built to last...Designed to Perform**



Model 39D-A
(Operator Side)

Specifications

Model Number	Dimensions			Voltage	Total Wattage	Approximate Weight		Kettle Capacity	Production Serving Per Hour
	Height	Width	Depth			Installed	Shipping		
39-A	25-1/8" (63.82 cm)	19-1/2" (49.53 cm)	14-1/4" (36.2 cm)	120 or 240V (AC only)	1197	45 lbs. (20.41 kg)	56 lbs. (25.4 kg)	6 Oz.	135 1 Oz.
39D-A	25-1/8" (63.82 cm)	21" (53.34 cm)	15-1/4" (38.74 cm)	120 or 240V (AC only)	1197	45 lbs. (20.41 kg)	56 lbs. (25.4 kg)	6 Oz.	135 1 Oz.
39R-A	25-1/8" (63.82 cm)	19-1/2" (49.53 cm)	14-1/4" (36.2 cm)	120 or 240V (AC only)	1197	45 lbs. (20.41 kg)	56 lbs. (25.4 kg)	6 Oz.	135 1 Oz.
39S-A	25-1/8" (63.82 cm)	19-1/2" (49.53 cm)	14-1/4" (36.2 cm)	120 or 240V (AC only)	1197	45 lbs. (20.41 kg)	56 lbs. (25.4 kg)	6 Oz.	135 1 Oz.

Typical Specifications

Popcorn machine shall be constructed of extruded aluminum corner posts and have 1/8" thick tempered glass panels and shall have two 3/16" thick plexiglass doors with full length aluminum hinges which provide easy access to the interior of cabinet. A clear lexan serving drop panel shall provide unobstructed merchandising. Popcorn machine shall be supplied with a 1000 Watt, 6 oz. capacity nickel plated steel popping kettle with a stainless steel exterior shell. A wire cage protected display lamp, heated stainless steel corn pan, and stainless steel old maid drawer shall be included as standard. Popper to be approved by Underwriters Laboratories and National Sanitation Foundation.